



Waveguide Transitions

Product Description

Waveguide transitions are available from 50 to 1100 GHz.

Length: 25mm

Flange: UG387/U-M precision flange

Material: bronze / brass

Surface finish: Gold plated

Applications:

- Measurement and Instrumentation
- Power measurements with WR10 calorimeters



Overview				
Type:	Part Number:	Insertion loss typ.	VSWR typ.	
WT-WR10-WR1.0	05300035	0,8 dB	1,06 : 1	
WT-WR10-WR1.2	05300034	0,7 dB	1,06 : 1	
WT-WR10-WR1.5	05300008	0,7 dB	1,06 : 1	
WT-WR10-WR1.9	05300028	0,5 dB	1,06 : 1	
WT-WR10-WR2.2	05300026	0,5 dB	1,06 : 1	
WT-WR10-WR2.8	05300000	0,3 dB	1,06 : 1	
WT-WR10-WR3.4	05300019	0,3 dB	1,03 : 1	
WT-WR10-WR4.3	05300020	0,25 dB	1,03 : 1	
WT-WR10-WR5.1	05300021	0,25 dB	1,03 : 1	
WT-WR10-WR6.5	05300001	0,2 dB	1,03 : 1	
WT-WR10-WR8	05300029	0,2 dB	1,03 : 1	
WT-WR10-WR12	05300024	0,15 dB	1,03 : 1	
WT-WR10-WR15	05300011	0,15 dB	1,03 : 1	